



P1 HEATSINK
 MAT'L: 6063-T5 ALUMINUM (AAVID EXTRUSION #72555)
 FINISH: ANODIZE PER MIL-A-8625, TYPE II, CL 2, BLACK
 TYPICAL BREAKDOWN VOLTAGE > 300V

- NOTES:**
1. UNLESS OTHERWISE NOTED, ALL DIMENSIONS ARE IN INCHES.
 2. BREAK ALL SHARP EDGES, DE-BURR & REMOVE LOOSE CHIPS.
 3. MARK WITH CONTRASTING INK AS SHOWN, IF SPECIFIED BY PURCHASE ORDER.
 4. THERMAL RATING: 1 °C/W
 5. APPROXIMATE WEIGHT: 14.9 oz [422g]

TOLERANCES - UNLESS OTHERWISE SPECIFIED		TITLE: MODULAR PACKAGE HEATSINK		MODEL: HS18	
.XX = ±.01 [.254]		SUBJECT: MECHANICAL DRAWING		ENGINEER: D-M	
.XXX = ±.005 [.127]		DRAWN BY: R.MOR		DATE: 03JAN14	
ANG. = ±5°		DCA: 13497		REV: J	
		SPL: 1		CP: 1	
		FILENAME: HS18			